

PrintMax[®] GP and PrintMax[®] ECON

High Impact Polystyrene

Product Description

PrintMax[®] HIPS Print Grade allows you to offer a wide range of industrial and signage and graphic arts applications with digital, litho, and Screen printing grades. Standard corona treatment is two-sided, but can be one-side corona treated upon request.

****Corona Treatment available up to 0.060" max"

Technical Properties

Digital/ Litho / Screen Grade

**** Corona Treatment available up to 0.060" max

	PrintMax [®] GP	PrintMax [®] ECON
Gauge Range	0.010" – 0.060"	0.020" – 0.060"

Gauge Tolerance:

+/-0.002" up to 0.030"
 +/- 5% for greater than 0.030"

Squareness Tolerance:

Up to 48" +/- 3/32"
 Over 48" +/-5/32"

Width Tolerance:

-0, +3/32"

Lay Flat Tolerance:

≤ .025" 3/32"
 >.025 5/32"

Length Tolerance:

0-63.999" -0, +3/32"
 64-98.999" -0, +1/8"
 99-122" -0, +1/4"

For questions regarding special sheet tolerances or other special requirements, please contact your local sales representative.

The manufacturer does not represent or warrant that this product will be suitable for all individual needs or applications. Spartech is committed to meet the specifications contained in this document, properties not outlined in this document are not warranted. It is the customer's sole responsibility to evaluate and confirm its fitness for its intended use or suitability for a specific application.

Acceptance of the product implies acceptance of this responsibility.