

Anti-Stat High Impact Polystyrene

Product Description

Anti-Stat High Impact Polystyrene sheet is designed for the multiple demanding applications that require a good balance of impact strength and heat deflection. This group of products can be specifically designed to comply with FDA Food Additive Regulation 21CFR177.1640 for rubber modified polystyrene.

Technical Properties

Property	Test Method	Value
Specific Gravity	ASTM D-792	1.04
Izod Impact (Notched) 72°F	ASTM D-256	2.4 ft-lbs/in
Heat Deflection Temperature @ 264 psi	ASTM D-648	185°F
Tensile Strength	ASTM D-638	2,500 psi
Tensile Elongation at Break	ASTM D-638	75%
Surface Resistivity	ASTM D-257	10^10 Ohms

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail <u>info@spartech.com</u> or visit our website at <u>www.spartech.com</u>

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.