

AquaPro® 30

Product Description

The AquaPro® product line features a uniquely engineered multi-layer thermoplastic composite sheet combining the appearance, chemical and weather resistance of specially formulated acrylic resins with the stiffness, impact strength and thermoforming characteristics of ABS. The outstanding balance of properties are designed for thermoformed sanitary ware applications including bathtubs, bathtub liners, bath wall surrounds, accessories and sinks.

Technical Properties

Property	Test Method	Value
Specific Gravity	ASTM D-792	1.06
Tensile Strength	ASTM D-638	5824 psi
Tensile Modulus	ASTM D-638	239885 psi
Tensile yield	ASTM D-638	3.50%
Tensile break	ASTM D-638	51.40%
Flexural Strength	ASTM D-790	9817 psi
Flexural Modulus	ASTM D-790	287236 psi
Rockwell Hardness (R Scale)	ASTM D-785	97
Heat Deflection Temperature (@264 psi - annealed)	ASTM D-648	210°F

**All values based on 0.125" unless otherwise stated*

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**