

# BK507 Black Masterbatch

## Product Description

Specially formulated Black Masterbatch to meet or exceed customer's expectations.

## Technical Properties

Property	Test Method	Value
Carrier Resin		PVC
Melt Flow Rate, 175°C/21.6kg	ASTM D-1238	100 g/10min
Bulk Density	Internal	51 lb/ft <sup>3</sup>
Pigment Loading (% ash)	Internal	38.7%
Pellet Weight	Internal	2.1 g/100 pellets
Volatile	Internal	0.12%
Specific Gravity	ASTM D-792	1.35
Hardness - Shore D	ASTM D-2240	89

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail [info@spartech.com](mailto:info@spartech.com) or visit our website at [www.spartech.com](http://www.spartech.com)

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**