

Post Industrial Recycled Content HIPS

High Impact Polystyrene

Product Description

Post Industrial Recycled High Impact Polystyrene sheet contains 50% up to 100% post-industrial recycled content. It is designed for applications needing a sustainable solution while providing impact strength that is fit-for-use in many applications.

Technical Properties

Property	Test Method	Value
Specific Gravity	ASTM D-792	1.04
Izod Impact (Notched) 72°F	ASTM D-256	>2.0 ft-lbs/in
Heat Deflection Temperature @264 psi	ASTM D-648	>180°F
Tensile Strength	ASTM D-638	>2,000 psi
Tensile Elongation at Break	ASTM D-638	>70%

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail <u>info@spartech.com</u> or visit our website at <u>www.spartech.com</u>

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.