

Floorlite TPR 3 FF

Flexible Sheet

Product Description

Floorlite TPR 3 is a custom solution for the transportation market. Our specialty formulated sheet incorporates 25 years of experience. Floorlite TPR 3's advanced characteristics provide a durable, formable solution to meet customer needs.

Technical Properties

Property	Test Method	Value*
Specific Gravity	ASTM D-792	0.917
Tensile Strength, MD	ASTM D-412	>1500 psi
Tensile Strength, TD	ASTM D-412	>1200 psi
Ultimate Elongation	ASTM D-412	940%
Hardness - Shore A	ASTM D-2240	94
Vicat Softening Temperature	ASTM D-1525	62°C
Izod Impact (Notched) ;73°F	ASTM D-256	No Break
Izod Impact (Notched) ;-23°F	ASTM D-256	12 ft-lbs/in
Flammability	FMVSS302	< 20 mm/min

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**