

UltraTuf APET MED

Rigid Co-Polyester Sheet

Product Description

UltraTuf APET MED sheet is excellent for rigid thermoformed packaging material. Crystal clear, this product offers exceptional clarity for applications demanding high product visibility. UltraTuf APET MED offers excellent printability, toughness, ease of fabrication and strong chemical resistance. Meets FDA Food Packaging Regulation 21CFR 177.1640 and the requirements of the U.S. Pharmacopoeia XXII Class making it an ideal choice for a variety of food and medical packaging applications.

Technical Properties

Property	Test Method	Value*
Specific Gravity (color dependent)	ASTM D-792	1.33
Heat Deflection Temperature (@264 psi)	ASTM D-648	149°F
Heat Deflection Temperature (@66 psi)	ASTM D-648	156°F
Vicat Softening Temperature	ASTM D-1525	176°F
Refractive Index	ASTM D-542	1.57
Haze (@ 0.25mm)	ASTM D-1003	0.80%
Flammability	UL 94-HB	Passes

*All values based on 0.125" unless otherwise stated

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail info@spartech.com or visit our website at www.spartech.com or visit our website at www.spartech.com or visit our website

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.